Specifications






Model	SP3006FM-L2	SP3010FM-L2	SP3012FM-L2	SP5012FM-L2
Hardware Version	V3	V3	V3	V2
Interfaces				
Downlink Ports	4 x 10/100/1000Mbps RJ45 ports	8 x 10/100/1000Mbps RJ45 ports	8 x 10/100/1000Mbps RJ45 ports	8 x 10/100/1000Mbps RJ45 ports
Uplink Ports	2 x 1000M/2.5Gbps SFP ports	2 x 1000M/2.5Gbps SFP ports	4 x 1000M/2.5Gbps SFP ports	4 x 1000M/2.5G/10Gbps SFP ports
Management Port	1 × Conslole Port			
IoT Interfaces	1*DI(Wet) 2-PIN Phoenix Type Connector (DI: Max input current: 3mA for state “0”: -30 VDC to 3 VDC; for state “1”: 12 VDC to 30 VDC) 1*Relay 2-PIN Phoenix Type Connector (1 relay outputs with current carrying capacity of 2A @ 30VDC ,0.3A @125V AC)			
PoE				
PoE Port	Port 1-4	Port 1-8		
PoE Standard	Port 1-2: 802.3af/at/bt Port 3-4: 802.3af/at	Port 1-2: 802.3af/at/bt Port 3-8: 802.3af/at		
PoE Pin Assignment	1/2(+), 3/6(-), 4/5(+), 7/8(-)			
PoE Power	90W Max. for port 1-2, 30W Max. for port 3-4 120W Max. (PoE power budget)	90W Max. for port 1-2, 30W Max. for port 3-8 240W Max. (PoE power budget)		
Performance				
Memony and Flash	Memory: 512MB Flash: 512MB			
Switch Property				
Forwarding Mode	Store and Forward			
Switching Capacity	18Gbps	26Gbps	36Gbps	96Gbps
Packet Forwarding Rate	13.4Mpps	19.3Mpps	26.8Mpps	71.4Mpps
MAC Address Table	16k			
Packet Buffer Memory	12Mbit			
Jumbo Frame	10kB			

Model	SP3006FM-L2	SP3010FM-L2	SP3012FM-L2	SP5012FM-L2
Power Supply				
Input Power	Power 1 (Main): 44~57V DC Power 2 (Backup): 44~57V DC			
Power Consumption	Idle: 8W 100% Traffic Rate with PoE: 128W	Idle: 10W 100% Traffic Rate with PoE: 250W	Idle:15W 100% Traffic Rate with PoE: 255W	Idle:18W 100% Traffic Rate with PoE: 258W
Physical Characteristics				
LED Indicators	**P** Off: the device is power off or failed Green On: the device power on is normal **S** Off: device system initialization Blinking: The system is working properly **Link** Off: ports link down On: ports link up Blinking: data on TX/RX **PoE** Off: PoE not working On: PoE working Fiber ports indicators Off: ports link down Green On: ports link up Green Blinking: data on TX/RX			
Fan Quantity	Fanless			
Switch Dimensions (W*D*H)	56*115*158 mm			
Package Dimensions	272*202*94 mm			
Weight	Net Weight: 1.15kg	Net Weight: 1.15kg	Net Weight: 1.18kg	Net Weight: 1.18kg
	Package Weight: 1.52kg	Package Weight: 1.52kg	Package Weight: 1.53kg	Package Weight: 1.53kg
Enclosure	IP40 metal case			
Installation	DIN-rail, Wall-mount, Desktop			

Model	SP3006FM-L2	SP3010FM-L2	SP3012FM-L2	SP5012FM-L2
Environmental				
Surge Immunity of Ethernet Port	IEC 61000-4-5 Common mode 6kV Differential mode 2kV			
Surge Immunity of Power	IEC 61000-4-5 Common mode 6kV Differential mode 4kV			
ESD Protection	IEC 61000-4-2 Contact discharge 8kV Air discharge 15kV			
Operating Environment	-40℃~75℃ (-40℉ to 167℉); 5%~90% (Non-condensation)			
Storage Environment	-40℃~85℃ (-40℉ to 185℉); 5%~95% (Non-condensation)			
Certification				
Certification	CE, FCC, RoHS, UKCA, RCM			

Model	SP3006FM-L2	SP3010FM-L2	SP3012FM-L2	SP5012FM-L2
Software Feature				
Port aggregation	Support 1GE port aggregation			
	Support 2.5GE aggregation(Only SP5012FM-L2 support 10GE aggregation)			
	Support static aggregation			
	Support LACP dynamic aggregation			
	Up to 64 aggregation groups and up to 8 ports per group			
Port features	Support IEEE802.3x flow control			
	Support port traffic statistics			
	Support Broadcast Storm (Broadcast; Unknown Multicast;Unknown Unicast)			
	Support Loop Detection（Port Based; VLAN Based)			
	Support Port mirroring（One-to-One; Many-to-One; Tx/Rx/Both)			
VLAN	Support Mac Based VLAN			
	Support IP Based VLAN			
	Support Protocol Based VLAN			
	Support GVRP（normal mode; fixed mode; forbidden mode)			
	Support QinQ（Port-based QinQ; VLAN-based QinQ; VLAN-based QinQ)			
Ring network protocol	Support IEEE 802.1D-STP			
	Support IEEE 802.1W -RSTP			
	Support IEEE 802.1S -MSTP			
	Support BPDU Guard			
	Support G.8032 ERPS protocol			
Routing protocol	Static routing			
DHCP	Support option-82			
	Support DHCP Client			
	Support DHCP Snooping			
L2 multicast	Support Group Address			
	Support IGMP snooping			

Model	SP3006FM-L2	SP3010FM-L2	SP3012FM-L2	SP5012FM-L2
ACL	Support IP Standard ACL			
	Support IP extend ACL			
	Support MAC extend ACL			
	Support L2, L3			
QoS	8 priority queues			
	802.1p CoS/DSCP priority			
	Queue scheduling (SP (Strict Priority); WRR(Weighted Round Robin)SP+WRR)			
	Rate Limit（Ingress /Egress Port; Egress Queue)			
mac-address	Static mac-address management			
	Dynamic mac-address management)			
	Filtering mac-address			
Security	Support RADIUS/TACACS+			
	Support Dot1x（port authentication, MAC authentication)			
	Support RADIUS authentication access switch (Telnet; SSH; HTTP; HTTPS)			
	Detect arp Message Filtering			
	Support IP Source Guard（Port-based IP/mac binding access)			
	Support port isolation			
IPV6	DHCP IPv6 Client			
	Ping IPV6			
	Tracert IPV6			
	Telnet IPv6			
	SNMP IPv6			
	SSH IPv6			
	Http IPv6			
	TFTP IPv6			
	Dual IPv4/IPv6			

Model	SP3006FM-L2	SP3010FM-L2	SP3012FM-L2	SP5012FM-L2
Management and maintenance	Support Syslog			
	Support RMON(1,2,3 &9)			
	Support NTP/SNTP(RFC2030)			
	Support Ping; TRACERT			
	Support optical transceiver DDM function			
	Support TFTP Client			
	Support TFTP, web upgrading			
	Configuration Export/import			
	Support IPv6 Management			
	Support PoE Management			
	Support relay Warning			
	Support Serial Server			