CARBON DIOXIDE

15LB CO2 FIRE EXTINGUISHER

MODEL: CO15LB

STANDARD COMPLIED WITH: DOT.ANSI/UL154





FEATURES:

Suitable for Class B and C Fires
Plated Brass Valve with Stainless Steel Handles
Aluminum Cylinder
100% Leak Tested
Production Under ISO9001 Quality System

LISTED LISTED USCG

TECHNICAL SPECIFICATION

Model Number	CO15LB
Capacity / lb (/kg)	15(6.8)
Cylinder Diameter / in (/mm)	6.89(175)
Height / in (/mm)	35.82(910)
Width / in (/mm)	11.42(290)
Discharge Time / s	14
Fire Rating	10-B:C
Extinguisher Weight / lb (/kg)	36.04(16.35)
Packing Size(L×W×H) / in (/mm)	11.62×7.28×26.77(295×185×680)
Discharge Range / ft (/m)	4-8(1.2-2.4)
Operation Temperature / F (/C)	-22~120(-30~49)
UL list File Number	EX 27916
Marine Type	B:C Size II
USCG Approval Number	162.028 EX 27916

* Transport Classification: Non-Flammable,Non-Toxic Gas.
UN No.1044 Class 2.2

Valve	 024314001	
Seal	0714025	
Lever	 0202148	
Rivet	 0204029	 0204021
Carry Handle	 0203125	
Valve Body	 020504042	
Bracket	 070200007	 070100016
Safety Gasket	 022304009	
Safety Disc	 0233007	
Safety Cap	 0212043	
O Ring	 020601126	 020601127
Valve Stem Assembly	 0220110	
Spring	 020701010	
Tube Holder	 020801036	
Dip Tube	080402048	
Cylinder	 050101173	
Safety Pin	 30420050	 020901033
Chain	0210001	
Connector	 0242022	
Hose Assembly	 080100047	
Hoop Assembly	 070200015	