AE-DC7351(OBDCABLE)
Power Cable



- Line length： Input line 0.45cm
- Wire specification： VIN3-core 17/0.15 2C yellow black 7/0.15 1C red
- Input requirements： Rated input voltage DC: 10-24V Maximum input current ≥1.5A
- Type of output： No-load output voltage DC: 5.0V ⎓ 2A Max
- Low power protection 11.3V±0.2v

▪ Specification

Interface	
Power Interface	Cable
General	
Power Supply	DC： 10-24V， 1.5A
Working temperature	-20 °C to 65 °C
Working humidity	95%(Max)

▪ Available Model

AE-DC7351(OBDCABLE)

▪ Accessory



AE-DC5113-F6S



Hi-D32F6/G



AE-DC5013-F6PRO



AE-DC2015-B1



AE-DC5313-C6



AE-DC5313-C6PRO



AE-DC5013-F6



AE-DC8012-C8



Hi-D20B1



AE-DC5013-F6S

Headquarters
No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com

Follow us on social media to get the latest product and solution information.

Hikvision HikvisionHQ HikvisionHQ Hikvision_Global Hikvision Corporate Channel hikvisionhq

©Hikvision Digital Technology Co., Ltd. 2023 | Data subject to change without notice |