DS-KEB30-AC
Access board



Access board for Speed gates & Turnstiles

- Support web server function, manage and configure functions through browser.
- Accessible to QR code readers and card readers (optional).
- Support fire access, linkage emergency door opening.
- Access control board kit for barrier products. (actual corresponding barrier model refer to product model names).

▪ Specification

System	
Operating system	Linux system
Network	
Wired network	100Mbps self-adaptive Ethernet
Wi-Fi	optional
Interface	
Network interface	1
Lock control	2
Exit button	2
Alarm output	2
RS-485	4
RS-232	3
Wiegand	Main: 1 Sub: 1
USB	1
Fire alarm input	1
Case input	2
Function	
Configuration via PC Web	Support
Configuration via mobile Web	Support
Anti-passback	Support
First person in	Support
Time synchronization	Support
Communication protocol	TCP/IP,ISAPI
General	
Power	24VDC 1A
Power consumption	20W
Working temperature	-40 °C to 70 °C (-40 °F to 158 °F)
Working humidity	10% to 95% (No Condensing)
Dimensions	Without casing： 150mm x 92mm x 16.6mm (5.9'' x 3.62'' x 0.65'')
Weight	0.2Kg (0.41lb)
Approval	CE/CB/RoHS/REACH/WEEE
Configuration	
Module selection	No

▪ Available Model

DS-KEB30-AC/K3G301X

DS-KEB30-AC/K3Y411BX

DS-KEB30-AC/K3G530X

DS-KEB30-AC/K3G200BX

DS-KEB30-AC/K3G225BX

DS-KEB30-AC/K3G501BX

DS-KEB30-AC/K3G411BX

DS-KEB30-AC/K6BC402X-R
DS-KEB30-AC/K6BC402X-R/868
DS-KEB30-AC/K6BC402X-RS
DS-KEB30-AC/K6BC402X-RS/868
DS-KEB30-AC/K3G501CX
DS-KEB30-AC/K3G411CX
DS-KEB30-AC/K3G225X
DS-KEB30-AC/K3G530X/Modular
DS-KEB30-AC/K3B530X/Modular
DS-KEB30-AC/K3G411CX/Modular
DS-KEB30-AC/K3G501CX/Modular
DS-KEB30-AC/K3B211X

▪ Accessory


DS-K3G411CLX


DS-K3G200BLX


DS-K3G225LX


DS-K3G530LX


DS-K3G501BLX


DS-K3G501CLX


DS-K3G301BLX

See Far, Go Further

www.hikvision.com
support@hikvision.com

© Hangzhou Hikvision Digital Technology Co., Ltd. Unless otherwise agreed, Hikvision makes no warranties, express or implied. We reserve the right to introduce modifications without notice.

HIKVISION®