DS-KEB05-LC
Lane Board



- Lane control board kit for barrier products. (actual corresponding barrier model refer to product model names).
- With fire input for linkage emergency door opening.

▪ Specification

Interface	
Exit button	Main: 2 Sub: 2
Fire alarm input	1
General	
Working temperature	-20 °C to 65 °C (04 °F to 149 °F)
Working humidity	0% to 95% (No condensing)
Dimensions	Without package: 164.2 mm × 32.6 mm × 95.7 mm (4.926" × 0.978" × 2.871")
Weight	0.2Kg (0.41lb)
Power supply method	24V DC

▪ Available Model

DS-KEB05-LC/K3G530X
DS-KEB05-LC/K3Y411BX-L
DS-KEB05-LC/K3Y411BX-R
DS-KEB05-LC/K3B211X-L
DS-KEB05-LC/K3B211X-R
DS-KEB05-LC/K6BC402X-L
DS-KEB05-LC/K6BC402X-R
DS-KEB05-LC/K3Y220X-R
DS-KEB05-LC/K3B220X-L
DS-KEB05-LC/K3B220X-R
DS-KEB05-LC/K3Y220X-L
DS-KEB05-LC/K3BC430X
DS-KEB05-LC/K3B530X-L
DS-KEB05-LC/K3B530X-R

See Far, Go Further

www.hikvision.com
support@hikvision.com

© Hangzhou Hikvision Digital Technology Co., Ltd. Unless otherwise agreed, Hikvision makes no warranties, express or implied. We reserve the right to introduce modifications without notice.

HIKVISION®