

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.


PANDUIT P/N	WEIGHT
SEE SHEET 2	SEE SHEET 2




LEFT VIEW




REAR VIEW



RIGHT VIEW



FRONT VIEW



BOTTOM VIEW

SPECIFICATION:

1. STANDARD

UNIT TYPE:	MONITORED INPUT
ORIENTATION:	VERTICAL, 0U MID
OUTLET QTY & TYPE:	(20)C13 , (4)C19
INPUT VOLTAGE:	200-240VAC
INPUT FREQUENCY:	50/60HZ
INPUT CURRENT:	30A(24A DERATED)
BREAKER QTY & TYPE:	(2)20AMP, DOUBLE-POLE
INPUT PHASE:	SINGLE-PHASE,L-L
RATED POWER:	5 KVA
INPUT PLUG:	NEMA L6-30P 3W
INPUT POWER CORD:	SEE SHEET 2 PART NUMBER TABLE
REGULATORY STANDARD:	UL 498 COMPLIANT

2. ADDITIONAL:
   NONE
3. ACCESSORIES:
   PRODUCT SAFETY WARNING SHEET

NOTES:

1. PRIMARY DIMENSIONS ARE IN MILLIMETERS. SECONDARY DIMENSIONS ARE IN [INCHES]
2. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL,STATE,AND LOCAL CODES
3. VISIT OUR ON-LINE CATALOG AT WWW.PANDUIT.COM FOR A CURRENT LIST OF PRODUCTS APPLICABLE FOR USE WITH THIS PART
4. FOR FULL PRODUCT FUNCTIONALITY REFER TO USER MANUAL
5. DRAWING VIEWS SHOW THE INPUT CORD IN THE "TOP END FED" CONFIGURATION

IDENTIFICATION:

FOR FINISHED GOOD PART NUMBER & DESCRIPTION TABLE SEE SHEET 2 CONFIGURABLE PART NUMBERS: E24D07M-XXYZ

- XX: FINISHED GOOD COLOR — BL = BLACK
- Y: INPUT FEED TYPE — 1 =TOP-END FED; 2 =BOTTOM-END FED
- Z: INPUT CORD LENGTH — C =3 METER

PLUG / RECEPTACLE BLOCK

PLUG
NEMA L6-30P 3W
30A, 250VAC MAX RATED INPUT

RECEPTACLE
IEC 60320 C13
10A, 240V MAX RATED OUTPUT

RECEPTACLE
IEC 60320 C19
16A, 240V MAX RATED OUTPUT

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
01A	06/01/2026	Mucl	MIM	MJD	UPDATE COMPLIANCE LABEL	E24D07M
00A	03/04/2026	Mucl	MIM	MJD	INITIAL RELEASE	E24D07M

PROJECT SPEC	SPS-EDI-611	PACKGING SPEC	1490×56×56
PART NUMBER	E24D07M	WORK INSTRUCTION	RD-01-02-25
INSPECTION INSTRUCTION NUMBER	QA-SIP-03	FMEA & CONTROL PLAN	PFMEA-P-01 CP-P-01

TITLE
INTELLIGENT SERIES PDU
E24D07M
CONTROL DRAWING

ITEM REVISION NAME:

DATASHEET FILE NAME:

UNLESS OTHERWISE SPECIFED
DIENSIONAL TOLERANCE ARE:mm [IN]

Tolerance(mm)	
0<L≤50	±0.5
50<L≤250	±1.0
250<L≤500	±1.5
500<L≤1000	±2.5
1000<L≤2000	±4.0

THIRD ANGLE PROJECTION

MATERIAL/COLOR: N/A

DRAWING NUMBER: E24D07M_DA

DRAWN BY	DATE	CHK	SCALE	SCALE
Mucl	06/01/2026	MIM	NONE	SHT 1 OF 3 — B

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

FINISHED GOOD PART NUMBER	FINISHED GOOD DESCRIPTION	COLOR	INPUT CORD LENGTH	WEIGHT
E24D07M	ES2P MI PDU, 30A(24A DERATED), (20)C13 (4)C19, NEMA L6-30P 3W-3M,TOP-FED, BLACK	BLACK(RAL 9005)	3M(+254MM/-127MM)[10'(+10"/-5")]	TBD

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
01A	06/01/2026	Mucl	MIM	MJD	UPDATE COMPLIANCE LABEL	E24D07M
00A	03/04/2026	Mucl	MIM	MJD	INITIAL RELEASE	E24D07M

PROJECT SPEC	SPS-EDI-611
PACKGING SPEC	1490×56×56
PART NUMBER	E24D07M
WORK INSTRUCTION	RD-01-02-25
INSPECTION INSTRUCTION NUMBER	QA-SIP-03
FMEA & CONTROL PLAN	PFMEA-P-01 CP-P-01

TITLE

INTELLIGENT SERIES PDU
E24D07M

CONTROL DRAWING

ITEM REVISION NAME:

DATASHEET FILE NAME:

PANDUIT

UNLESS OTHERWISE SPECIFED
DIENSIONAL TOLERANCE ARE:mm [IN]

THIRD ANGLE PROJECTION

Tolerance(mm)	
0<L≤50	±0.5
50<L≤250	±1.0
250<L≤500	±1.5
500<L≤1000	±2.5
1000<L≤2000	±4.0

MATERIAL/COLOR: N/A

DRAWING NUMBER: E24D07_DA

DRAWN BY	DATE	CHK	SCALE	SCALE
Mucl	06/01/2026	MIM	NONE	B

SHT 2 OF 3

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PANDUIT P/N	WEIGHT
SEE SHEET 2	SEE SHEET 2

SEE NOTE 3.

PANDUIT
18900 Panduit Drive, 60487, USA
www.panduit.com

Model/Modelo: S1-DD024SV
Input/Entrada:200-240VAC,1Ø, 50/60Hz, 24A
Output per Outlet/Salida por Receptáculo:
C13; 200-240VAC, 10A per outlet
C19; 200-240VAC, 16A per outlet
24A Total
TAA COMPLIANT

Power Distribution Unit / Unidad de distribución de Energía


CAN ICES-003(A)/NMB-003(A)
Exclusivo para uso interior.
Prohibido su uso en exteriores.
No modificar ni reparar.
Revisarla periodicamente.
Desconectarla cuando no se utilice.
No sobrepasar la corriente indicada.
Conectar la clavija totalmente.
Temperatura máxima de operación: 60°C
Calibre:15.3mm² Largo: 3m

UPC & SKU Barcode

Serial # & MAC Address

Made in / Hecho en TAIWAN

COMPLIANCE LABEL



INTERNAL WIRING SCHEMATIC

NOTES:
1.INTERNAL WIRING:
WIRE TYPE: UL AWM 1015, 12 & 18AWG
LINE COLOR: BROWN
NEUTRAL COLOR: BLUE
EARTH GROUND COLOR: GREEN/YELLOW STRIPE
2.REFERENCE PANDUIT ENGINEERING PRODUCT SPECIFICATION SPS-EDI-611 FOR ADDITIONAL PRODUCT INFORMATION NOT SPECIFIED ON THIS DRAWING
3.FOR FINISHED GOOD PART NUMBER AND DESCRIPTION, SEE TABLE ON SHEET 2

LINE COLOR ANNOTATION IN SCHEMATIC:
RED:18AWG WIRE
PINK:12AWG WIRE
GREEN:3×10AWG WIRE
LIGHT BLUE: NETWORK CABLE
DARK BLUE: CT CABLE

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
01A	06/01/2026	Mucl	MIM	MJD	UPDATE COMPLIANCE LABEL	E24D07M
00A	03/04/2026	Mucl	MIM	MJD	INITIAL RELEASE	E24D07M

PROJECT SPEC	SPS-EDI-611	PACKGING SPEC	1490×56×56
PART NUMBER	E24D07M	WORK INSTRUCTION	RD-01-02-25
INSPECTION INSTRUCTION NUMBER	QA-SIP-03	FMEA & CONTROL PLAN	PFMEA-P-01 CP-P-01

TITLE
INTELLIGENT SERIES PDU
E24D07M
CONTROL DRAWING

ITEM REVISION NAME:

DATASHEET FILE NAME:

PANDUIT

UNLESS OTHERWISE SPECIFED
DIENSIONAL TOLERANCE ARE:mm [IN]
THIRD ANGLE PROJECTION

Tolerance(mm)	
0<L≤50	±0.5
50<L≤250	±1.0
250<L≤500	±1.5
500<L≤1000	±2.5
1000<L≤2000	±4.0

MATERIAL/COLOR: N/A

DRAWING NUMBER: E24D07M_DA

DRAWN BY	DATE	CHK	SCALE		SCALE
Mucl	06/01/2026	MIM	NONE	SHT 3 OF 3	B