VIA GO3

Compact & Secure 4K Wireless Presentation Device

| HDMI | Ethernet - RJ-45 | 4K/30 UHD



VIA GO3 gives iOS, Android, Chromebook, PC, and Mac users instant wireless connectivity with 4K advanced presentation capabilities. The product features content streaming with crystal−clear mirrored images and stunning video playback and includes iOS mirroring via AirPlay™, Windows & Android mirroring via Miracast™, as well as Chromebook mirroring. VIA GO3 is super−compact (9x9cm) and flexible to install, with both built−in Wi−Fi and LAN connectivity and includes industry−leading 1024−bit encryption for secure use on the internal network

FEATURES

Quick and Reliable Wireless Connectivity - A simple and intuitive user interface enables iOS, Android, Chromebook, PC, and Mac device users to instantly connect to a main display without a dongle. 2.4GHz/5GHz Wi−Fi and MIMO antennas establish and maintain a fast and reliable connection

Clientless Connectivity - Airplay, Miracast, join through browser

High Quality Video Streaming - Supports up to 4K resolution (using the VIA app Multimedia feature)

Auto Discover and Auto Join - A user can find neighboring VIA devices using the BLE tab and Auto Join in the case of a single discovery. If more than one nearby device is found, click Join on desired IP address

Built-In Wi-Fi, LAN, and Bluetooth

- Smooth Network transition within the same gateway while switching from wireless Network to LAN connection

Preview - In Active Directory Moderator Mode, the moderator can preview the content of a presentation before allowing it to present

Simultaneous Display - Four participants can simultaneously present content on main display

Cloud-Based Management - VIA Site Management (VSM) cloud−based web application used to manage and configure large numbers of VIA devices from anywhere

Easy and Flexible Installation - With a super−compact 9x9cm form factor, it can be discreetly installed on the back of a display, projector or almost anywhere

Present Privately (DND) Feature - Allows the presenter to continue the presentation without being interrupted

Pause/Resume Presentation - Present at your convenience

TECHNICAL SPECIFICATIONS

Ports	1 Ethernet: On an RJ-45 connector
	3 USB 3.0: On a female USB type-A connector
Outputs	1 HDMI: 2.0 On a female HDMI connector
Control	Management VSM on Cloud
Video	Max Resolution: Up to 4K Output
General	Networking: 1 x Gigabit LAN Wi-Fi 802.11 ac/b/g/n dual band & Bluetooth
	Operating System: Linux
Power	Source: 12V DC
	Consumption: 3.8A
Accessories	Included: Power adapter
Environmental Conditions	Operating Temperature: 0° to +40°C (32° to 104°F)
	Storage Temperature: -40° to +70°C (-40° to 158°F)
	Humidity: 10% to 90%, RHL non-condensing
Regulatory Compliance (Standards Compliance)	Safety: CE, FCC, UL, BIS
Enclosure	Type Aluminium cooling, fan with sink, Kensington lock
	Dimensions 89.9mm x 89.9mm x 36mm (3.54" x 3.54" x 1.42")
Product Dimensions	9.00cm x 9.00cm x 3.50cm (3.54" x 3.54" x 1.38") W, D, H
Product Weight	0.2kg (0.5lbs) approx
Shipping Dimensions	15.90cm x 11.90cm x 11.10cm (6.26" x 4.69" x 4.37") W, D, H
Shipping Weight	0.9kg (1.9lbs) approx



